

SPECIFICATIONS:

FORM FACTOR:

- PCIe x4 Rev 1.0a
- Full Height, Full Length PCIe (12.3" x 3.8")

POWER REQUIREMENTS

Approximately 25 watts (3.3VDC @ 4 Amps, 12VDC @ 1.2 Amp)

ENVIRONMENTAL

- Operating Temp: 10 C to 40 C
- Storage Temp: -40 C to 65 C
- Relative Humidity: 10 to 80% non-condensing
- ROHS Compliant

ORDERING INFORMATION:

- **CP-LVDT-RVDT-SIM**
8-channel LVDT/RVDT Simulation Package
- **WC-CP-FIO**
RedHawk™ Driver for FPGA-based I/O cards
- **ICS-SWB-1276**
License for Programmable FPGA card use under SIMulation Workbench

Note: The CP-LVDT-RVDT-SIM model number supports the above functionality only. If additional features are required, a programmable FPGA PCIe card (CP-FPGA-2) is required.

More Information:

concurrent-rt.com
wiki.simwb.com
info@concurrent-rt.com
800.666.4544
954.974.1700

About Concurrent Real-Time: Concurrent Real-Time is the industry's foremost provider of high-performance real-time computer systems, solutions and software for commercial and government markets.